OPEN TOP



Ratings	20' Open Top	40' Open Top
Maximum Gross Weight	30,480 kg (67,200 lb.)	30,480 kg (67,200 lb.)
Tare Weight	2,300 kg (5,070 lb.)	3,920 kg (8,640 lb.)
Payload	28,180 kg (62,129 lb.)	26,560 kg (58,557 lb.)
External Dimensions		
Length	6,058 mm (19'-10")	12,192 mm (40'-0")
Width	2,438 mm (8'-0")	2,438 mm (8'-0")
Height	2,591 mm (8'-6")	2,591 mm (8'-6")
Internal Dimensions		
Length	5,895 mm (19'-2")	12,029 mm (39'-1")
Length (between top headers)	5,680 mm (18'-5")	11,806 mm (38'-4")
Length (between corner gussets)	5,457 mm (17'-7")	11,531 mm (37'-5")
Width	2,352 mm (7'-6")	2,352 mm (7'-6")
Width (between top rails)	2,252 mm (7'-4")	2,232 mm (7'-3")
Height	2,348 mm (7'-7")	2,348 mm (7'-7")
Height (under top rail)	2,252 mm (7'-3")	2,012 mm (6'-5")
Door Opening		
Width	2,340 mm (7'-6")	2,340 mm (7'-6")
Height	2,280 mm (7'-4")	2,280 mm (7'-4")
Cube		
Cubic Capacity	32.5 m³ (1,150 ft.³)	65.9 m³ (2,326.9 ft.³)
Fork Pocket Dimensions		
Width	360 mm (1'-2")	
Height	115 mm (4.6")	
Pitch	2,050-2,080 mm (6'-7"-6'-8")	
Gooseneck Tunnel		
Length		3,290 mm (10'- 9 1/2")
Width		1,029 mm (3' - 4 1/2")
Height		120 mm (4 3/4")
Roof Structure		
Roof bows:	8 pieces galvanized steel tube pitch of 690 mm (2'-2").	19 pieces galvanized steel tube pitch of 610 mm (2').
Tarpaulin:	550-600 gm/meter sq. PVC coated.	550-600 gm/meter sq. PVC coated.
Customs cable:	PVC covered galvanized steel cable.	PVC covered galvanized steel cable.